

# **BAND SEALER**

ITEM/PARAMETER/MODEL	FRD-750 I (HORIZONTAL)	FRD-750 II (VERTICAL)
VOLTAGE (V/Hz)	AC 220/ 50	
MOTOR POWER(W)	80 W	
SEALING POWER(W)	300*2	
SEALING SPEED (M/MIN)	0~12	
SEALING WIDTH (MM)	10 MM	
TEMPERATURE CONTROL RANGE	0~300 °C (STEPLESS ADJUSTABLE)	
MAX.OVERALL LOADING OF CONVEYOR(KG)	≤6	
MAX.SINGLE PACKAGE LOADING OF CONVEYOR(KG)	≤2	
EXTERNAL DIMENSIONS(L*W*H) MM	844*375*310MM(HORIZONTAL) 844*390*450MM(VERTICAL)	
NET WEIGHT (KG)	23 KG-HORIZONTAL,28 KG(VERTICAL)	

- SUITABLE FOR SEALING INDIVIDUAL POUCHES /BAGS AUTOMATICALLY
- IT HAS VARIABLE TEMPRATURE CONTROLLER AND SPEED CONTROL TO SUIT DIFFERENT GRADE OF PLASTIC MATERIALS

**PACK FASTLY WITH BEST QUALITY AND PERFECTION**

